



Fresenius Medical Care

## Fresenius Medical Care North America Service Bulletin

Equipment: 2008K Hemodialysis Machines

Bulletin: 07-FRK-001 Rev. B

Subject: New Circuit Boards (Update)

Originated By (Dept.):	Reviewed By	Approved By	Effective Date
J. Fox (TSD)	K. Cogswell	CN044866	01/16/13

Distribution: Dir TS (B. La Bier), Sr Mgr FS (M. Lucas), TS Mgr (K. Cogswell), Dir QS (G. Chambers), QE (M. Mohr), Eng (C. Woods), Prod Mgr (M. Singer, G. Reny), FMS TS Mgr (J. Barr), Canada (T. Greene), Mexico (J. Narango)

### 1.0 PURPOSE

To inform all Field Service and Technical Support personnel of the release of a new Actuator/Test Combo board (P/N 190234-XXX\*) and a new Motherboard (P/N 190232) for the 2008K Hemodialysis machine.

- \* The -XXX indicates the software version programmed on the part number 190234 Actuator/Test Combo board.  
For example: 190234-101 is an Actuator/Test Combo board with software version 1.01.

### 2.0 SCOPE

The Actuator/Test Combo board replaces the need to have a Test board in the card cage and makes room for further expansion options. The 190232 Motherboard adds the capability of allowing the Actuator/Test Combo board to replace the Actuator board and to eliminate the need for a Test board.

### 3.0 DETAILS

The new Actuator/Test Combo board replaces the separate Actuator and Test boards. It uses the same motherboard position as the original Actuator board. In order to use the Actuator/Test Combo board the following apply:

- The Functional software must be V3.29 or greater.
- To eliminate the need for a Test board, the Motherboard must be part number 190232. If you don't have this Motherboard you can still use the Actuator/Test Combo board as an Actuator board but you must have a Test board installed and have Functional software V3.29 or greater.

The Actuator/Test Combo board does not change any machine functions. The calibration processes remain the same, as well as all other Service Mode configurations.


The software on the Actuator/Test Combo board is no longer stored on an EPROM and is updated using a method similar to the Functional board.

It is recommended to conduct the Voltage Detection Calibration whenever an Actuator or Actuator/Test Combo board is replaced. Refer to the 2008K Calibration Procedures (P/N 507296).

Figure 1 and Figure 2 on the following pages are illustrations of the Actuator/Test Combo board and the 190232 Motherboard respectively.

If there are any questions regarding this bulletin, contact Fresenius Technical Support at 800-227-2572.

© 2007 - 2013, Fresenius Medical Care North America, All rights reserved.



**Figure 1 – Actuator/Test Combo Board  
(P/N 190234-XXX\*)**

\* The –XXX indicates the software version programmed on the part number 190234 Actuator/Test Combo board. For example: 190234-101 is an Actuator/Test Combo board with software version 1.01.

